


3054 FILMING AMINES ANALYZER



The 3054 is the latest analyzer in the Waltron 3040 Series of colorimetric analyzers. The 3040 Series is trusted world wide to deliver accurate and reliable readings with minimal maintenance and low total cost of ownership. Common applications are boiler cycle water and process water.

FEATURES



- Accurate and wide-range analysis
- Multi-stream available
- Fast loop reservoir
- Adjustable cycle and calibration frequency
- Automatic calibration and validation (QA/QC)
- Compact design
- Color touchscreen display
- Grab sample capability
- Internal datalogger
- Low reagent level alarm
- No compressed air required
- Automatic start/stop based on sample flow detection
- Minimal analyzer maintenance



See reverse side for specifications.



Wet Section



3054 FILMING AMINES ANALYZER | GENERAL SPECIFICATIONS

PERFORMANCE

Range	0-500ppb
Accuracy	+/- 10 ppb or +/- 5% of reading, whichever is greater
Reproducibility	+/- 5% of reading
Analysis Time	9 min, batch process
Sampling Frequency (Cycle Time)	One reading every 20 mins, adjustable
Required Maintenance	Monthly replenish reagents; Quarterly replace tubing
Reagent Consumption (approximate)	3 reagents, 2.5L each per month
Sensor Classification	Colorimetric with glass flowcell and LED source
Application	Boiler water and cooling water
Ambient Temperature Range	10-45°C analyzer (50-113°F)
Atmospheric Pressure Range	No Limits
Humidity	Up to 90% not condensable
Unit Dimensions	Height=23.6"(60 cm), Width=15"(38 cm), Depth=8.3"(21 cm)
Positioning and Installation Details	Wall mounting, bench supported, or panel mounting (optional)
Weight	17 kg (37.5 lbs.)
Degree of Protection	IP55 (NEMA 4): Wet section, IP65 (NEMA 4x): Electronics
Alarms	2 or 4 configurable alarm relays (Result, loss of sample, fault)
Power Supply	110-220Vac, 50-60 Hz 80 VA
Certification (on request)	Meets low voltage and low electromagnetic compatibility directives

SAMPLE DELIVERY OPERATING CONDITIONS

Temperature Range	5-55°C (41-131°F)
Inlet Sample	100-500 ml/min, atmospheric, flexible tubing O.D. 1/4"(6 mm)
Outlet Sample	Atmospheric, waste tubing O.D. 3/8"(9 mm)
PH	3-12
Sample Conditioning Requirements	Filtering between 10 and 60 micron, depending on the matrix, needed only to avoid clogging.
Materials in Contact with Sample	Glass, Silicone, Plexiglass, Stainless Steel AISI 316

SIGNAL OUTPUTS

Analog Outputs	4-20mA (galvanic isolator module available as option) or 0-5V
Serial I/O Options	RS232; RS485; MODBUS; PROFIBUS

OPERATIONAL CALIBRATION

Single/Multi Point	Multi-Point: zero and mid range
Matrix Corrections	Yes, sample blank correction
Manual/Automatic	Both

102-046-B.1



WALTRON GROUP HEADQUARTERS

25 Minneakoning Road, Suite 101

Flemington, NJ 08822 USA

Phone: +1 908 534 5100

Fax: +1 908 534 5546

www.waltron.net